

DESCRIPTION

OSCH-144 has 6 fiber cable in-out round ports for the cable diameter $\Phi 13$ - $\Phi 15$ mm entry. It is widely applied to the splicing and distributing variable optical cables.

It is made of high-quality ABS plastic and with the mechanical seal structure filled with the seal material. The external component and fastening piece are all made of the high-quality steel. It can be opened after sealing and can be reused without changing sealing material, with silicone rubber insulation tape.

SPECIFICATION:

- Dimension (mm) 466.5x179.8x120.6
- Weight (Kg) 2.7
- Cable diameter $\Phi 13$ - $\Phi 15$
- cable entry ports 3 in 3 out
- Max Capacity of splice tray 6
- Max Capacity 72 (single layer tube) 144 (double layer tube)
- Sealing structure silicon gum material or sticky



APPLICATIONS

FTTH access network / Telecommunication Networks / CATV Networks / Data communications Networks / Local Area Networks




STREET



HOSPITAL



INDUSTRIES



FTTH



OTHERS

ACCESSORIES:

- Splice protector sleeve
- Silicon gum material
- Sticky cincture
- Cable ties
- Sealing washer
- Allen wrench
- Insulated rubber belt



SPECIFICATIONS

MODEL	MAX.CAPACITY	DIMENSION	MATERIAL	SPLICE TRAY
OSCH-144	144	466.5x179.8x120.6	ABS	6PCS